









Ground-recessed luminaire for discharge lamps and compact fluorescent lamps.
Coated die-cast aluminium structure.
Stainless steel outer ring.
Protection louver in tempered glass (15 mm).
Complete with power-factor-corrected electromechanical ballast.
Complete with electrical device for single or series connection.
M24 cable clamp for H07RN-F cable.

SQUARE HILL

DESIGN - QUATTROBI TECHNICAL DEPARTMENT

| CODE | DESCRIPTION | |
|------|---|---|
| 1490 | Maxi Square Hill - Asymmetrical optical component MT (CDM-T) - 35W - G12 - 230V - 50Hz Colour: stainless steel - IP 67 - IP 65 IK08 mechanical shocks 2000 Kg static load Supplied with H07RN-F cable 3x1 mm ² Complete with power-factor-corrected electromechanical ballast |   T 85°C |
| 1491 | Maxi Square Hill - Symmetrical optical component MT (CDM-T) - 35W - G12 - 230V - 50Hz Colour: stainless steel - IP 67 - IP 65 IK08 mechanical shocks 2000 Kg static load Supplied with H07RN-F cable 3x1 mm ² Complete with power-factor-corrected electromechanical ballast |   T 75°C |
| 1492 | Square Hill - Light blade optical component MT (CDM-T) - 35W - G12 - 230V - 50Hz Colour: stainless steel - IP 67 - IP 65 IK08 mechanical shocks 2000 Kg static load Supplied with H07RN-F cable 3x1 mm ² Complete with power-factor-corrected electromechanical ballast |   T 75°C |
| 1493 | Maxi Square Hill - Symmetrical optical component FSQ (TC-D) - 18W - GX24q-2 - 230V - 50Hz Colour: stainless steel - IP 67 - IP 65 IK08 mechanical shocks 2000 Kg static load Supplied with H07RN-F cable 3x1 mm ² Electronic ballast |   T 60°C |



ACCESSORIES

996 Recessed box in coated die-cast aluminium

